TECHNICAL DATA SHEET



Name: ANT0438 - PATINA NOCE SCURO A STRACCIO
Code: ANT0438
Identification: SOLVENT-BASED STAIN
Revision: Rev.2 - 11/2026

Features

Solvent based, wet glaze base used to define and enhance interior wood furniture and cabinets. It is designed to be used with PUR and acrylic Topcoats and Sealers to produce unique finishing effects and grain enhancement. Application may be by hand or spray. Reducible with white spirit.

Technical Specifications

ANT0438	Property	Specification	Unit	Method
	Solid Content	70,0 - 75,0	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Never apply the glaze to bare wood. This product has been specifically formulated to be applied over a properly sealed surface. Recommended seal coats include pigmented and clear 2K sealers. Catalyzed systems should be dried a minimum of 24 hours prior to glaze application. Seal coats must be thoroughly dried and sanded with a minimum of 220 grit sandpaper prior to glaze application.
It is recommended to stir well the product before use. Apply the product by spraying or with a rag. Allow two to three minutes air-drying before wiping. Wet glaze should be dried for a minimum of 4 hours at room temperature prior to top coating. Longer dry times may be necessary if drying conditions are less than ideal.
After wiping, brush blending, highlighting and complete drying, it can be overcoated by a suitable system. It is critical that any excess glaze is removed from the work surface prior to the application of the topcoat or poor adhesion will result.

Application methods

Dipping	☐	Spraying	☑	Roller	☐	Brush	☑
Cloth	☑	Spatula	☐	Flow-coating	☐		

Application

	Drying time	Around 4 hours at 20°C (with good ventilation)
	Overcoating	After about 5 hours at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard packaging size of 25 Kg; for other requests a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 10 - 26
The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it