TECHNICAL DATA SHEET



Name: ANT0500 Series - ANTICATURA
Code: ANT0500 Series
Identification: ANTIQUE EFFECT STAIN
Revision: Rev.2 - 11/2026

Features

Antique effect stain for application with a spray gun, on wood or woody material, ethanol-based.
Available in various colour tones.
Also gold colour shade.

Technical Specifications

ANT0500 Series	Property	Specification	Unit	Method
	Density (20°C)	0,82 - 1,30 (depending on the colour)	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	08 - 15 (depending on the colour)	Sec.	IST 11/08
	Viscosity, Din Cup 4 (20°C)	06 - 12 (depending on the colour)	Sec.	IST 11/09

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

The antique effect stains from the ANT0500 series are ready to use, they can be diluted with ethyl alcohol according to need in order to achieve the desired effect.
Apply with a spray gun and remove any excess with Scotch Brite, or fine steel wool.

Application methods

Dipping	☐	Spraying	☑	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

	Media type	2K primer
	Surface preparation	Preliminary sanding – sanding paper 280 - 320
KG	Recommended amount	30 - 50 gr/m² (recommended)
	Useful time for steel wool refinishing	20' at 25°C (with good ventilation)
	Overcoating	After 2 hours

TECHNICAL DATA SHEET



Name: ANT0500 Series - ANTICATURA
Code: ANT0500 Series
Identification: ANTIQUE EFFECT STAIN
Revision: Rev.2 - 11/2026

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.
SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it