TECHNICAL DATA SHEET



Name: ANT0668 PATINA NOCE
Code: ANT0668
Identification: ANTIQUE EFFECT STAIN
Revision: Rev.2 - 11/2026

Features

Solvent based antique effect stain, Walnut coloured, for application with a spray gun, on wood or woody material. It is designed to be used with PUR and acrylic Topcoats and Sealers to produce unique finishing effects and grain enhancement.

Technical Specifications

ANT0668	Property	Specification	Unit	Method
	Density (20°C)	0,82 - 0,86	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	08 - 12	Sec.	IST 11/08

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Never apply the product to bare wood. This product has been specifically formulated to be applied over a properly sealed surface.
It is recommended to stir well the product before use.
Apply the product by a spray gun, Allow the product to dry accurately before remove any excess. Once the product has dried, remove any excess with Scotch Brite, or fine steel wool.
To protect this patina, you can apply polyurethane varnish, "nitro" varnish or water-based varnish.

Application methods

Dipping	☐	Spraying	☑	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

	Media type	2K primer
	Recommended amount	30 - 50 gr/m² (recommended)
	Useful time for steel wool refinishing	20' at 25°C (with good ventilation)
	Overcoating	After 2 hours

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 10 - 26
The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it