# TECHNICAL DATA SHEET




**Name:** ANT0726 PATINA DAIMLER V530 E@MBEAM 3D HOLZ
**Code:** ANT0726
**Identification:** SOLVENT-BASED STAIN
**Revision:** Rev.2 - 11/2026

## Features

Solvent-based stain for spray-application on wood veneer, characterized by fast drying and good lightfastness.
To protect this finish, you can apply polyurethane paint, “nitro” paint, polyester paint, or water-based paint.

## Technical Specifications

| ANT0726 | Property | Specification | Unit | Method |
|---|---|---|---|---|
| | Density (20°C) | 0,90 - 0,94 | Gr/cc | IST 11/01 |
| | Ford Cup 4 Viscosity (20°C) | 09 - 11 | Sec. | IST 11/08 |
| | Dry Residue | 3,0 - 8,0 | % | IST 11/06 |

*The values describe the typical properties of the product. Technical Specifications are available upon request.*

## Use

The stain is ready to use. Apply using a spray gun with a 1.3-millimeter nozzle and a pressure of 2 or 3 atmospheres.
It is recommended to stir well the product before and during use.

## Application methods

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Dipping | ☐ | Spraying | ☑ | Roller | ☐ | Brush | ☐ |
| Cloth | ☐ | Spatula | ☐ | Flow-coating | ☐ | | |

## Application

| | |
|---|---|
| Recommended amount | 30 - 50 gr/m² (recommended) |
| Dust free | About 15’ at 20°C (with good ventilation) |
| Overcoating | After about 4 hours at 20°C (with good ventilation) |

## Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard packaging size of 20 Kg; for other requests a feasibility evaluation will be made.

## Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

**SERVIND ITALY s.r.l.** - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it