TECHNICAL DATA SHEET



Name: APV0071 - BESCHLEUNIGER 10 TIX-NON-TIX
Code: APV0071
Identification: ACCELERATOR
Revision: Rev.1 - 11/2026

Features

Liquid accelerator additive for industrial applications, specific for unsaturated polyester products. The additive can also be used as accelerator for alkyd-based paints and drying oils in order to accelerate the drying of the film.

Technical Specifications

APV0071	Property	Specification	Unit	Method
	Density (20°C)	0,91 - 0,95	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 11	Sec.	IST 11/08

Use

Depending on the Insaturated-Polyesters Varnish used.
The added amount depends on the normal drying speed of the product and is however deductible through practical tests.
Stir well after adding.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

The application characteristics can only be evaluated in combination with the paint that is used.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 0.5 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it