TECHNICAL DATA SHEET



Name: APV0110 - ADDITIVO ANTICRATERE
Code: APV0110
Identification: ANTI-CRATER ADDITIVE
Revision: Rev.1 - 11/2026

Features

Surface additive for solvent systems, with a strong reduction in surface tension, very effective for wetting critical supports and to avoid craters.
Non ha nessuna influenza sulle proprietà di “slip” della superficie.

Technical Specifications

APV0110	Property	Specification	Unit	Method
	Density (20°C)	0,88 - 0,92	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 11	Sec.	IST 11/08
	Solid Content	01 - 04	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

The APV0110 product is added from 1 to 5% in weight, on the total weight of the formulation. In exceptional cases it can be added up to 10% in weight.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

The application characteristics can only be evaluated in combination with the paint that is used.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it