TECHNICAL DATA SHEET



Name: APV0112 - ADDITIVO LIVELLANTE
Code: APV0112
Identification: LEVELING ADDITIVE
Revision: Rev.1 - 11/2026

Features

Surface additive for solvent paints containing silicone, with a strong reduction in surface tension.
Excellent substrate wetting agent, prevents the formation of craters and increases surface slip.

Technical Specifications

APV0112	Property	Specification	Unit	Method
	Density (20°C)	0,88 - 0,92	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 11	Sec.	IST 11/08
	Solid Content	10 - 12	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Add the product to the paint in a ratio of 1 to 10% by weight.
It is recommended to stir it in well for 5 minutes during its addition.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

The application characteristics can only be evaluated in combination with the paint that is used.

Also check that the added quantity does not create problems in over-applications with other paint products.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it