TECHNICAL DATA SHEET



Name: ISI 1011 P46 SOLVENTBASED CONCENTRATE
Code: ISI 1011
Identification: SOLVENTBASED STAIN CONCENTRATE
Revision: Rev.2 - 11/2026

Features

Solventbased pigmented stain concentrate, for both spray and rag application on wood or wood-like materials, characterised by good drying speed and excellent overpaintability.

Technical Specifications

ISI 1011	Property	Specification	Unit	Method
	Viscosity, Ford Cup 4 (20°C)	12 - 16	Sec.	IST 11/08
	Solid Content	5,0 - 8,0	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

It is recommended to stir well the product before use.
Before use, ISI 1011 is to be diluted 1:1 with DPV 0646. Apply by spraygun with nozzle of 1.3 - 1.6 mm and pressure of 2.0-3.0 bar.

Application methods

Dipping	☐	Spraying	☑	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

Dust free	About 15' at 20°C (with good ventilation)
Overcoating	After at least 4 hours at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard packaging size of 25 Kg; for other requests a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 10 - 26
The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it