TECHNICAL DATA SHEET



Name: PPS XX Fluo Series - PASTE PIGMENTATE FLUO
Code: PPS XX Fluo Series
Identification: CONCENTRATED PIGMENT PASTE
Revision: Rev.1 - 11/2026

Features

Solvent-based colouring paste, usable in combination with Converters of the Databook P&C tinting system, to obtain lacquer paints with the characteristic Fluo colors. Available in various colour tones, from Fluo Green to Fluo Red.
The lacquer, produced with PPS XX Series Fluo pastes, do not have external stability over time.

Technical Specifications

PPS XX Fluo Series	Property	Specification	Unit	Method
	Density (20°C)	1,00 - 1,20	gr/cc	IST 11/01
	Solid Content	72 - 78	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Add the PPS XX Fluo Series pigmented pastes to the transparent Converters of the Databook P&C tintometric system in a suggested quantity of 25%. It is recommended to stir it well for 5 minutes after its addition.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

Apply the product according to the indications suggested in the technical data sheet of the used Converter.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between +4°C and +35°C) that is not subject to abrupt temperature excursions. Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it