TECHNICAL DATA SHEET



Name: PPS0064 - PASTA BIANCA HYDRO
Code: PPS0064
Identification: CONCENTRATED PIGMENT PASTE
Revision: Rev.1 - 11/2026

Features

White pigmented paste in an aqueous suspension, for use in the wood industry in small quantities to correct defects in wood veneer or in medium quantities for formulating coloured dyes.

Technical Specifications

PPS0064	Property	Specification	Unit	Method
	Density (20°C)	2,06 - 2,10	gr/cc	IST 11/01

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

The pigmented paste can be added to the topcoat in the order of 5% maximum to correct defects due to the veneer or added in a maximum concentration of 30% to a water formulation to prepare coloured dyes. Stir well after adding.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

The pigmented paste can be applied either by spraying or by rag/brush.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it