TECHNICAL DATA SHEET



Name: PPS0353 - PASTA BLACK FOR PIANO LOOK
Code: PPS0353
Identification: CONCENTRATED PIGMENT PASTE
Revision: Rev.1 - 11/2026

Features

Solvent-based black pigment paste for use in the wood industry in small quantities to colour varnish based on unsaturated polyester .

Technical Specifications

PPS0353	Property	Specification	Unit	Method
	Density (20°C)	1,08 - 1,12	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	Thixotropic (t>= 180")	Sec.	IST 11/08
	Solid Content	90 - 100	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Add the pigmented paste to the unsaturated polyester based paint in a variable amount between 1 and 3 wt %, depending on the desired effect. It is recommended to stir it well for 5 minutes after its addition.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

Evaluate depending on the paint used with the PPS0353.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 20°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it