TECHNICAL DATA SHEET



Name: PPT 02 Series - PASTES
Code: PPT 02 Serie
Identification: PIGMENTED PASTES
Revision: Rev.1 - 11/2026

Features

Solvent-based colouring paste, usable in combination with converters, both acrylic and polyurethane, in order to obtain lacquer paints.
Available in various colour tones.

Technical Specifications

The technical specifications are supplied on request, according to colour.

Use

The solvent-based pigmented pastes from the PPT 02 Series may be added to converters, both acrylic and polyurethane, according to the following recommendation:
- KOPP white converters at 95% by weight + PPT 02 Series pigmented pastes at 5% by weight.
- KOPT o KOAT clear converters at 75% by weight + PPT 02 Series pigmented pastes at 25% by weight.
Refer to the data sheets of the converters, for the preparation and final characteristics of mixed products.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

The pigmented pastes from the PPT 02 Series when mixed with the appropriate converter can be applied by airless spray, airmix or gravity cup.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it