TECHNICAL DATA SHEET



Name: PTS0013 - PASTA TESTURIZZANTE MEDIA
Code: PTS0013
Identification: TEXTURING PASTES
Revision: Rev.1 - 11/2026

Features

Medium texturizing paste, for applications on wood or wood-based materials, to use in small quantities in solvent-based Varnish, Polyuretanics or Acrylics to lend to the varnished surfaces a rough, but pleasant to the touch, texture.

Technical Specifications

PPT0013	Property	Specification	Unit	Method
	Density (20°C)	0,88 - 0,92	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	Thixotropic (t>= 180")	Sec.	IST 11/08
	Solid Content	45,0 - 55,0	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Add the PTS texturizing paste in a quantity equal to 10% to the paint to Texturize. It is recommended to stir it well for 5 minutes after its addition. Proceed with hardening, thinning and applying, following the specific indications of the paint used.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

Evaluable depending on the paint used with it.

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it