TECHNICAL DATA SHEET



Name: SML Series - FILLER
Code: SML Series
Identification: FILLER
Revision: Rev.2 - 11/2026

Features

Single component filler for wood, characterized by minimum loss of thickness and good sandability. Ideal to repair small defects in the wood.
Intended for interior applications, available in various colour tones.

Technical Specifications

SML Series	Property	Specification	Unit	Method
	Solid Content	60 - 70	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

The single-component filler from the SML series is ready for use, for spatula applications.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☑	Flow-coating	☐		

Application

Sandable	About 3 hours at 20°C (with good ventilation)
Overcoating	After about 3 hours at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 40°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 10 - 26
The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it