TECHNICAL DATA SHEET



Name: TAI Series - IDRO SM
Code: TAI Serie
Identification: WATER-SOLUBLE ACRYLIC-BASED PAINT
Revision: Rev.2 - 11/2026

Features

Acrylic-waterbased stain for application with flow-coating, spray gun or deeping, on wood or wooden materials, characterise from fast drying time and optimal overcoatibility.
To protect this finish, you can apply polyurethane paint, “nitro” paint, polyester paint, or water-based paint.
Available in various colour shades.

Technical Specifications

The technical specifications are supplied on request, according to colour.

Use

The paints from the TAI Series are ready for use. To apply it, use a spray gun having a nozzle from 1.2 to 1.6 millimetres with a pressure of 2 to 3 atmospheres.
It is recommended to stir well the product before use.

Application methods

Dipping	☐	Spraying	☑	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

Recommended amount	30 - 50 gr/m² (recommended)
Drying time	Approx. 1 hour at 25°C
Overcoating	After about 5 hours at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard packaging size of 25 Kg; for other requests a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 10 - 26
The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it