TECHNICAL DATA SHEET



Name: VES GOLD Series - PASTE 1K GOLD TOPCOAT
Code: VES02-03 GOLD SERIES
Identification: SINGLE-COMPONENT METALLIC GOLD PAINT
Revision: Rev.1 - 11/2026

Features

Single-component solvent-based paint, for application with normal or electrostatic spray gun, able to confer to the surface a looks similar to matt gold. The product has direct adhesion on wood and woody matherials, and upon appying the suitable primers, on metals, plastics and MDFs . Highly resistant to scratches, wear and thermal shock, according to the products used as topcoat.
Non-yellowing product suitable for both indoor and outdoor items, depending on the amount of cycles used.
Available in the following shades: VES0299 (gold) - VES0300 (green/gold) - VES0301 (pale gold) - VES0302 (red/gold) - VES0347 (bright pale rich gold) - VES0348 (bright pale gold) - VES0354 (champagne).

Technical Specifications

VES02 - 03 GOLD Series	Property	Specification	Unit	Method
	Density (20°C)	0,94 - 0,98	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	32 - 38	Sec.	IST 11/08
	Solid Content	20 - 24	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Thin the Product with DPV0006. The thinning of the product is established at the time of application according to the application parameters present, recommended at 50% by weight.
When a better product spreading is required, it is recommended to add a small amount of retardant thinner DPV0026 to the mix.
Apply two coats of product with an interval of about 3 - 5 minutes.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐		
Cloth	☐	Spatula	☐	Flow-coating	☐				

Application

	Suggested amount	90 - 120 gr/m²
	Dust free	About 15' at 20°C (with good ventilation)
	Overcoating interval	From a minimum of 20' to a maximum of 6 hours
	Stacking	After about 24 hours at 20°C (with good ventilation)

TECHNICAL DATA SHEET



Name: VES GOLD Series - PASTE 1K GOLD TOPCOAT
Code: VES02-03 GOLD SERIES
Identification: SINGLE-COMPONENT METALLIC GOLD PAINT
Revision: Rev.1 - 11/2026

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it