TECHNICAL DATA SHEET



Name: VES0082 - FINITURA CRAQUELET
Code: VES0082
Identification: CRACKLE EFFECT FINISH
Revision: Rev.1 - 11/2026

Features

Single-component solvent finish based on acrylic polymers, for spray applications on various types of materials. the crackle effect is a technique used for lending a worn and aged look to products, imitating an old paint that crackled over time, with cracks branching in all directions.
Intended for interior applications.

Technical Specifications

VES0082	Property	Specification	Unit	Method
	Density (20°C)	0,90 - 0,94	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	10 - 12	Sec.	IST 11/08
	Solid Content	09 - 11	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

Apply the product on a support previously treated with VES0148. To the crackle finish of VES0082, add the pigment pastes to obtain the desired colour (the weight ratio between paints and pigment pastes should be 10: 1), thin with DPV0021 to obtain a fine crackle effect, or with DPV0026 to obtain a coarser crackle effect.
For spray application, use a 1.8 mm nozzle (recommended minimum), at a pressure of no more than 2.5 atmospheres. The amount of material applied must be constant over the entire surface, since the thickness applied has a direct influence on the final effect.
To get the best performance in terms of design and adhesion, the interaction with other supporting products is of the utmost importance, please contact our technical service.

Application methods

Dipping ☐ Spraying ☐ Roller ☐ Brush ☐
Cloth ☐ Spatula ☐ Flow-coating ☐

Application

Dust free	About 60' at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it