TECHNICAL DATA SHEET



Name: VES0288 - METAL MIRROR EFFECT SB
Code: VES0288
Identification: MIRROR EFFECT
Revision: Rev.1 - 11/2026

Features

Single-component solvent-based coat, for spray applications on various types of materials, able to confer to the surface a look similar to chrome.. Medium resistant to scratches, wear and thermal shock, according to the products used as topcoat. Non-yellowing product suitable for both indoor and outdoor items, depending on the amount of cycles used.

Technical Specifications

VES0288	Property	Specification	Unit	Method
	Density (20°C)	0,87 - 0,91	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	11 - 15	Sec.	IST 11/08
	Solid Content	0 - 2	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

Use

The product is ready for use; Apply with a spray gun having a nozzle from 0.5 to 1.0 millimeters and with a pressure of 2 to 3 atmospheres.
For best results it is recommended to apply the product on a black and glossy primer suitable for the material on which you want to apply the product. The application of topcoat is reccommended after 24hours.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

	Suggested amount	10 - 20 gr/m²
	Dust free	About 15' at 20°C (with good ventilation)
	Overcoating interval	From a minimum of 20h to a maximum of 36 hours
	Stacking	After 24 hours at 20°C (with good ventilation)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 30°C) that is not subject to abrupt temperature excursions. Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

TECHNICAL DATA SHEET



Name: VES0288 - METAL MIRROR EFFECT SB
Code: VES0288
Identification: MIRROR EFFECT
Revision: Rev.1 - 11/2026

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it