TECHNICAL DATA SHEET



Name: VES0359 - 1K CONCRETE EFFECT WB
Code: VES0359
Identification: WATERBASED 1K
Revision: Rev.1 - 11/2026

Features

One-component water-based paint, cement effect, with a rough texture and the appearance of cement, applicable by spray on wood or wood-like materials. Because of the wide variety of substrates, compatibility with the substrate to be painted must be tested beforehand on a sample of the material.

Technical Specifications

VES0359	Property	Specification	Unit	Method
	Density (20°C)	1,10 - 1,20	gr/cc	IST 11/01
	Dry Matter	68 - 76	%	IST 11/08

Use

Before application, the wood should be sealed with a primer. The cement effect can be colored as desired with water-based coloring pastes. Before application, the primer should be sanded with 180 grit. Dilution of the product is determined at the time of application depending on the application parameters present, recommended at 20% to 50% by weight with water. Apply by blending with a spray gun having a nozzle of 5.0 to 8.0 millimeters and a pressure of 2 to 3 atmospheres.
Immediately after application, various effects can be worked on with paper or squeegee. To facilitate surface cleaning, we recommend applying a top coat with a low gloss level.

Application methods

Dipping	☐	Spraying	☐	Roller	☐	Brush	☐
Cloth	☐	Spatula	☐	Flow-coating	☐		

Application

	Suggested amount	120 - 250 gr/m²
	Dust free	Circa 6 hours at 20°C (with a good ventilation)
	Stacking	After about 16 to 24 hours at 20°C (depending on the thickness)

Storage and packaging

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 30°C) that is not subject to abrupt temperature excursions.
Standard packaging of 5 kg. For other required specifications, a feasibility assessment will be carried out.

Safety precautions

The product is intended for professional use only, refer to the Safety Data Sheet.

The data shown refer to laboratory tests; in practical applications they may vary significantly depending on the application conditions. The user must in any case verify the suitability of the product for the intended use and assumes all responsibility arising from its use. SERVIND ITALY reserves the right to make technical changes without prior notice.

SERVIND ITALY s.r.l. - Via Palmanova 62/1 - 33048 San Giovanni al natisone - (UD) ITALY - Phone: +39 0432 756261 - Fax +39 0432 756630 - info@servind.it - www.servind.it